

CACTUS 15

DRIES RESIN IN 30 MINUTES GUARANTEED!



Description:

The Cactus 15 will process up to 30 lbs/hr of most engineering resins.

The Cactus dryer is mounted directly on the feed throat of the molding machine. A hopper or loader is mounted to the top of the dryer to provide a continuous supply of resin to the dryer. The resin is supplied directly from the bag, barrel or gaylord and does not require pre-drying

Technical Data:

Height	(in)	28
Ship Weight	(lbs)	54
Air Consumption	(cfm)	2
Electrical	(kw)	1.4
230V, 1 Phase	(amps)	6.1
Heated Capacity	(lbs)	6
Total Capacity	(lbs)	8

THROUGHPUT GUIDE LBS/HR

ABS	30
ACETAL	75
ACRYLIC	30
BUTYRATE	15
NYLON	30
PBT (VALOX)	30
PET (RYNITE)	15
POLYCARBONATE	30
POLYETHYLENE	75
POLYSTYRENE	75
POLYSULPHONE	15
POLYURETHANE	15
PPO (NORYL)	30
ULTEM	15
PVC	30
SAN	30

CACTUS MACHINERY LLC. - 1570 Georgetown Rd.
Hudson, OH 44236 PN:330-650-9280 FX: 330-653-3052
Web: www.cactusmachinery.com
E-mail: sales@cactusmachinery.com

