

CACTUS 5

DRIES RESIN IN 30 MINUTES GUARANTEED!



Description:

The Cactus 5 will process up to 7 lbs/hr of most engineering resins.

The Cactus dryer is mounted directly on the feed throat of the molding machine. A hopper or loader is mounted to the top of the dryer to provide a continuous supply of resin to the dryer. The resin is supplied directly from the bag, barrel or gaylord and does not require pre-drying.

Technical Data:

Height	(in)	18
Ship Weight	(lbs)	26
Air Consumption	(cfm)	1
Electrical	(kw)	0.75
230V, 1 Phase	(amps)	3.3
Heated Capacity	(lbs)	1
Total Capacity	(lbs)	2

THROUGHPUT GUIDE LBS/HR

ABS	7
ACETAL	15
ACRYLIC	7
BUTYRATE	3
NYLON	7
PBT (VALOX)	7
PET (RYNITE)	3
POLYCARBONATE	7
POLYETHYLENE	15
POLYSTYRENE	15
POLYSULPHONE	3
POLYURETHANE	3
PPO (NORYL)	7
ULTEM	3
PVC	7
SAN	7

CACTUS MACHINERY LLC. - 1570 Georgetown Rd.
Hudson, OH 44236 PN:330-650-9280 FX: 330-653-3052
Web: www.cactusmachinery.com
E-mail: sales@cactusmachinery.com

